S4A INDUSTRIAL CO.,LIMITED



Shockproof Guard Tour Systems With 1.8inch LCD Display



Product Introduction

6200C and 6200D are the same series of products, with impact recording technology and mass memory of 80,000 logs. Built-in rechargeable battery reduced sabotage from a security guard.

2 in 1 USB cable for data downloading and battery charging. Pogo pin contacts make the device more durable to resist communication corrosion and damage.

Features

- 1. Auto induction, free pressing any button.
- 2. Swiss EM reading technology, Read 125kHzEM(ID) tags.
- 3. Metal shell, waterproof, shake-proof, high/low temperature resistant.
- 4. Pogo pin communication interface, vandal-resistant.
- 5. 32,000pcs impact record memory capacity, well documented for device damage.
- 6.80,000 pcs mass memory capacity.
- 7. Stylish appearance and Hang rope design, easy to carry.
- 8. 3.7v rechargeable built-in lithium battery, data cable charging directly.
- 9. LED flickering and vibration for operation prompt.

Application

- 1) Security guard touring on housing area (Property building)
- 2) Telecommunications communication fibre and equipment regular check logging
- 3) Electricity power supply line, voltage transformer regular patrol check data logging
- 4) Hotel, buildings housekeeping logging
- 5) Storage warehouse security patrol round control
- 6) Security person patrol touring for Oil, coal mine, Chemical Equipment, petroleum pipeline and oil wells
- 7) Hospitals nurse attendance for patient care data logging
- 8) Production links monitoring on a factory workshop
- 9) School security patrolman's regular touring monitoring logging
- 10) Policeman/army safety inspection circular data logging.

Electronic guard tour system can be used in any area where there is with strict safety control and time-bound request.

Specifications

Reading technology	Read 125kHz EM(ID) tags proximity
Storage capacity	80,000 pieces
Impact records capacity	32,000 pieces
Communication	USB cable
Operation prompt	LED +vibration
Baud rate	115200
Work power consumption	30mA
Working temperature	-20°C ~ 70°C
Working humidity	30%~90%
Battery	3.7v built-in rechargeable lithium battery, data cable charge directly
Standard accessories	Data cable, safety protective cover, charger plug, software

GUARD TOUR SYSTEM SOLUTION



